Derungs
MEDICAL LIGHTING

TRIANGO 60
The compact one that has what it takes



TRIANGO 60 – your new treatment & minor surgery light

TRIANGO 60 C
ceiling version



TRIANGO 60 W
wall mount



TRIANGO 60 F
roller stand



TRIANGO 60 F Battery
roller stand





TRIANGO 60	technical data
Fitted with	1× LED-Modul
Luminous power *	60 000 Lux / 1,0 m
Colour temperature * TRIANGO 60-1 F TRIANGO 60-3 F	fixed value 4 700 K changeable value 3 700 / 4 300 / 4 700 K
Lighting field 1,0 m*	ø 18 cm
Depth of illumination *	140 cm
Colour rendering index *	Ra > 94
Operation equipment	Electronic converter
Voltage	100-240 V; 50/60 Hz
Luminaire body	Polyamide (PA)
Power consumption	< 30 W
Usage	Touch panel on cardanic system
Technology	Single-pole secondary
Balance of articulation joints	Spring (weight compensation)
Class of protection	I
Protection rating	IP 43 (illumination head) IP 20 (UPSmedv Pack)
Standards met	EN 60601-1, EN 60601-2-41

Special features	
TRIANGO 60-1	• Continuously dimmable
TRIANGO 60-3	• Continuously dimmable • 3 colour temperatures
TRIANGO Fokus 60-1	• Continuously dimmable • Focusable
TRIANGO 60-1 F Battery	• Continuously dimmable • UPSmed Pack
Mounting	• Ceiling mount • Wall mount • Roller stand
Cord length TRIANGO 60-1 C TRIANGO 60-1 W TRIANGO 60-1 F TRIANGO 60-1 F Battery	 Direct power supply Direct power supply 3 m 3 m
Weight (net) TRIANGO 60-1 C TRIANGO 60-1 W TRIANGO 60-1 F TRIANGO 60-1 F Battery	 13 kg 12,5 kg 19 kg 31 kg
Accessories	• Sterilizable handle • Disposable cover for handle

*** -10% / +20% tolerance**

Homogeneous light field
thanks to unique diamond optic

Versatile
versions with focusable or colour changeable illumination field

Easy cleaning
streamlined design and the removable handle



Hygiene made simple
good design does without unnecessary details and attaches importance to closed building structures

Can be used everywhere
TRIANGO 60 is suitable for the versatile daily routine in family practices and clinics as well as in gynecology, dermatology or veterinary medicine



Ergonomic handling
easy alignment for right- and left-handed



Intuitive operation
thanks to an intuitive touch panel on the cardanic, the illumination from 60 000 lux at 1 m can be infinitely adjusted

Order number: TRIANGO 60-1	
TRIANGO 60-1 C	D16.250.000-00813741 D16.253.000-00814312 - USA
TRIANGO Fokus 60-1 C	D16.252.000-00814311 D16.255.000-00814314 - USA
TRIANGO 60-1 W	D16.256.000-00813742 D16.274.000-00814327 - USA
TRIANGO Fokus 60-1 W	D16.258.000-00814316 D16.276.000-00814329 - USA
TRIANGO 60-1 F	D16.262.000-00813744 - CH D16.259.000-00813743 - Schuko D16.271.000-00813747 - UK D16.265.000-00813745 - USA
TRIANGO Fokus 60-1 F	D16.264.000-00814320 - CH D16.261.000-00814318 - Schuko D16.273.000-00814326 - UK D16.270.000-00814322 - USA
TRIANGO 60-1 F Battery	D16.279.000-00814482 - CH D16.278.000-00814481 - Schuko D16.282.000-00814485 - UK D16.280.000-00814483 - USA

Order number: TRIANGO 60-3	
TRIANGO 60-3 C	D16.251.000-00814310 D16.254.000-00814313 USA
TRIANGO 60-3 W	D16.257.000-00814315 D16.275.000-00814328 USA
TRIANGO 60-3 F	D16.263.000-00814319 - CH D16.260.000-00814317 - Schuko D16.272.000-00814325 - UK D16.266.000-00814321 - USA

NEW

5 YEARS WARRANTY
for all electrical components

MDR CERTIFIED
European Medical Device Regulation

SWISS Engineering

MADE SWISS

TÜV SÜD
tuvsud.com/ps-cert

Headquarters

Derungs Licht AG
Hofmattstrasse 12
9200 Gossau
Switzerland
+41 71 388 11 66
mailbox@derungs.swiss
www.derungs.swiss

Derungs Licht AG is
a company of the
Waldmann Group

www.derungs.swiss

Register and benefit:
+ 1 year warranty and
exclusive offers

www.derungs.swiss/product-registration

ENG | © Derungs Licht AG · D80.262.000-00814394 · Printed: 06/2023 · Digital update: 07/2023 · Subject to modifications · Printed in Switzerland